Note   Committed gloves   Insulated gloves   Insulated gloves   Insulated gloves   Insulating materials thick comply to prevent leakage 400V insulating   It contains 2 kg of 40% MAP (Mono ammanium phasphate) based powder. It extinguishes the fames by sufficiating the first transfer to statistic to MAP.   Prowder extinguishes the fames by sufficiating the first transfer to statistic to MAP.   Prowder extinguishes the fames by sufficiating the first transfer to statistic to MAP.   Prowder extinguishes the fames by sufficiating the first transfer to statistic to MAP.   Prowder extinguishes the fames by sufficiating the first transfer to statistic to MAP.   Prowder extinguishes the fames by sufficiating the first transfer to statistic tra
Anti-electrostatic gloves and of insulating materials thick enough to prevent leakage 400V insulating  teontains 12 kg of 40% MAP (Mono ammonium phosphate) based powder:  teotinguishes the Hamse's by suffocating the fire thanks to MAP.  Powder extinguishers:  12 kg  Powder extinguishers:  12 kg  Powder extinguishers:  13 kg of 40% MAP (Mono ammonium phosphate) based powder:  teotinguishes the Hamse's by suffocating the fire thanks to MAP.  He contains 12 kg of 40% MAP (Mono ammonium phosphate) based powder:  teotinguishes the Hamse's by suffocating the fire thanks to MAP.  He contains the fire cap are fire it is a subject to the contains the fire thanks to MAP.  Working pressure is between 15-18 Bar.  Serving plasmae as 14 median and high expansion properties.  Foam fire extinguishers and the combustion temperature, creating a colling material, cut off oxygen and reduce the combustion temperature, creating a colling material, cut off oxygen and reduce the combustion temperature, creating a colling material, cut off oxygen and reduce the combustion temperature, creating a colling for enks.  Product Technical Features  Represented with Ntrogen Gas, which allows the liquid inside to escape several plants and short the long distance as 5 means and the long of the sexual several plants and short the long of the sexual several plants and short the long of the sexual several plants and short the long of the sexual several plants and short the long of the sexual several plants and short the long of the sexual several plants and short the long of the sexual several plants and short the long of the sexual several plants and short the long of the sexual several plants and short the long of the sexual several plants and short the long of the sexual several plants and short the sexual several plants and short the sexual several severa
ammonium phosphate) based powder. It stringulables the flames by sufforcating the fire thanks to MAP. It is used in AB-C class fires, (A: solid fire 8: biguid fire C, gas fire). It is used in AB-C class fires, (A: solid fire 8: biguid fire C, gas fire). It is used in AB-C class fires, (A: solid fire 8: biguid fire C, gas fire). It is pressure with Nitrogen Gas that allows the dust inside to come out.  Working persure is between 15-18 Bar. Spraying Distance 4-3 meters Safety valve trigger mechanism  It contains 6 liters of foam with medium and high expansion properties. Foams cover the surface of the burning material, cut off coveger and reduce the combustion temperature, creating a cooling extention of the combustion temperature, reating a cooling extended file of the combustion temperature, reating a cooling extended file of the combustion temperature, reating a cooling extended file of the combustion temperature, reating a cooling extended file of the combustion temperature, reating a cooling extended file of the combustion temperature, reating a cooling extended file of the combustion temperature, reating a cooling extended file of the combustion temperature, reating a cooling extended file of the combustion temperature, reating a cooling extended file of the combustion temperature, reating a cooling extended file of the combustion temperature, reating a cooling extended file of the combustion temperature, reating a cooling extended file of the combustion temperature, reating a cooling extended file of the combustion of the combus
Foam fire extinguishers are suitable for environments with Class A (solid) and Class B (liquid) fire risks. Product Technical Features it is pressurized with Nitrogen Gas, which allows the liquid inside to escape. Working pressure is between 15-18 Bar. Spraying Distance 4-5 meters Safety valve trigger mechanism  4 Shovel  A steel agricultural shovel with a wooden handle 1.6 m long.  To open closed doors and spaces Metal metal devices used during fires made of heat-resistant steel ranging in length from 60 to 100 cm used to open windows  Metal stick  high expansion properties. Foams cover the surface of the burning material, cut off oxygen and reduce the combustion redequals allowed by the combustion temperature, creating a cooling effect. Foam fire extinguishers are suitable for environments with Class A (solid) and Class B (liquid) fire risks. Product Technical Features It is pressurized with Nitrogen Gas, which allows the liquid inside to escape. Working pressure is between 15-18 Bar. Spraying Distance 4-5 meters Safety valve trigger mechanism  A steel agricultural shovel with a wooden handle 1.6 m long.  To open closed doors and spaces Metal metal devices used during fires made of heat-resistant steel ranging in length from 60 to 100 cm used to open windows  To open closed doors and spaces Metal metal devices used during fires made of heat-resistant steel ranging in length from 60 to 100 cm used to open windows
wooden handle 1.6 m long.  To open closed doors and spaces Metal metal devices used during fires made of heat-resistant steel ranging in length from 60 to 100 cm used to open windows  To open closed doors and spaces Metal stick  To open closed doors and spaces Metal metal devices used during fires made of heat-resistant steel ranging in length from 60 to 100 cm used to open windows  To open closed doors and spaces Metal stick  To open closed doors and spaces Metal metal devices used during fires made of heat-resistant steel ranging in length from 60 to 100 cm used to open windows  To open closed doors and spaces Metal stick  To open closed doors and spaces Metal metal devices used during fires made of heat-resistant steel ranging in length from 60 to 100 cm used to open windows  To open closed doors and spaces Metal metal devices used during fires made of heat-resistant steel ranging in length from 60 to 100 cm used to open windows
Metal stick Metal stick Metal stick Metal stick Metal registant steel ranging in length from 60 to 100 cm used to open windows  Metal stick Metal stick of heat-resistant steel ranging in length from 60 to 100 cm used to open windows  Metal stick Piece and Decision of the street of
To open closed doors and spaces ror Iron cutting roscissors used during fires dedicated to cutting metal quickly made of steel with very sharp blades resistant to corrosion length ranges from 40 to 60 cm
7 Water transport container 20 liter capacity 20-liter water pail used to extinguish fires made of metal with light weight and easy to carry 20 liter capacity 20 liter capacity 20 liter capacity 20 liter water pail used to extinguish fires made of metal with light weight and easy to carry 20 liter capacity 20 liter capacity 20 liter capacity 20 liter water pail used to extinguish displayed to extinguish fires made of metal with light weight and easy to carry
Fire blanket measuring (150cm-180cm) Made of 100% Fiber glass Resistant to high temperature 550-900 ° C and non- flammable. And ensures that the fire is extinguished by throwing it on the fire at the beginning of the fire. Its weight at least 900 grams. Fabric thickness not less than 0.4 mm. With the same specifications of: EN 1869:1997 Packaged in a textile bag, with printed name and instructions for use, closed with a nylon interlocking closure, and has a metal lug for hanging on the walls.  Fire blankets  Risid through a subject of 100% Fiber glass Resistant to high temperature 550-900 ° C and non- flammable. And ensures that the fire is extinguished by throwing it on the fire at the beginning of the fire. Its weight at least 900 grams. Fabric thickness not less than 0.4 mm. With the same specifications of: EN 1869:1997 Packaged in a textile bag, with printed name and instructions for use, closed with a nylon interlocking closure, and has a metal lug for hanging on the walls.  Risid with the same specifications of: EN 1869:1997 Packaged in a textile bag, with printed name and instructions for use, closed with a nylon interlocking closure, and has a metal lug for hanging on the walls.
for night usages Night light for use during fires made of heat- resistant materials Equipped with a strong battery that can be recharged for long periods Waterproof and dustproof  for night usages Night light for use during fires made of heat- resistant materials Equipped with a strong battery that can be recharged for long periods Waterproof and dustproof  for night usages Night light for use during fires made of heat- resistant materials Equipped with a strong battery that can be recharged for long periods Waterproof and dustproof  Piece ada  185
It must have all mandatory first aid materials (wounds and fire injuries type)  As shown in the attached table below.  It must have all mandatory first aid materials (wounds and fire injuries type)  As shown in the attached table below.  Kit
Safety jackets, Antifire gloves, fire helmet The fire proof suit is made of fireproof and waterproof materials with two layers of insulation inside and outside that reduce heat transfer to the body - Heat-insulating gloves protect hands from fire and sharp materials Made of fire-resistant leather and synthetic fibers - Helmet made of heat-resistant  Set  Javanua  Javan
fiberglass or plastic with a liftable face shield - Fireproof leather shoes resistant to heat and water resistant to slipping and splinters from the front It has a metal head to protect the toes
fiberglass or plastic with a liftable face shield - Fireproof leather shoes resistant to heat and water resistant to slipping and splitters from water resistant to slipping and splitters from

محتويات حقيبة الإسعافات الأولية / Contents of first aid kit								
#	Description	الوصف		Unit	quantity	Unit cost	Total cost	
2	Adhesive bandages of various sizes	ضمادات لاصقة بأحجام مختلفة		packet عبوة	2			
3	elastic bandage wrap:Rollelast Bandages Elastic Bandage Medical elastic bandage with permanent elasticity, soft and durable structure and air permeable. Allergic.Does not affect blood circulation.Can be washed in warm water and reused. Can be used in fractures, dislocations and sprains, soft tissue contusions and varicose veins, traumas due to sports impacts and injuries. DETAILED INFORMATION • Soft and durable structure • Air permeable • Does not cause sweating • Does not affect blood circulation • Reusable	ضمادات رول لاست ضمادة مرنة ضمادة مرنة طبية ذات مرونة دائمة وبنية ناصة وموتية ونفاذة للهواء. لا تسبب الحساسية المدوية. لا تقوش على الدورة الدموية. يمكن غسلها في ماء داق وإعادة استخدامها. يمكن استخدامها في الكسور والخلع والالتواءات وكدمات يمكن غسالتها في الكسور والخلع والالتواءات وكدمات والإصابات الرواضية. والإصابات الرواضية. معلومات مفصلة • بنية ناعمة ومتينة • نفاذة للهواء • لا تسبب التعرق • لا تؤثر على الدورة الدموية • قابلة لإعادة الاستخدام	The Roll Elist	Piece قطعة	2			
4	Triangular sling/bandages (safety pins included)	حيال/ضمادات مثلثة الشكل (تتضمن دبابيس أمان)		Piece قطعة	1			
5	Medical adhesive wrap	غلاف طبي لاصق طبي	Formula (Control of the Control of t	Wrap لفافة	2			
6	Thermometer: Non-contact infrared digital body and forehead thermometer is a CE-certified FDA-approved product. It works with 2 AAA batteries. In body temperature mode: It measures between 32 - 42.9 degrees. The main advantage of this device is a non-contact method for determining temperature. It has a special infrared sensor that captures the heat emitted by the body, captures and displays the values on the screen.	ميزان حرارة: مقياس الحرارة الرقبي للجسم والجبهة بالأشعة تحت الحمراء بدون تلامس هو منتج معتمد من إدارة الغذاء والدواء الأمريكية وحاصل على شهادة CE. يعمل ببطاريتين AAA. درجة. درجة. الميزة الرئيسية لهذا الجهاز هي طريقة عدم التلامس لتحديد درجة الحرارة. يحتوي على مستشعر خاص بالأشعة تحت الحمراء ويعرضها على الشاشة.	365	Piece قطعة	1			
7	Medical cotton balls: 200 gr	كرات القطن الطبية: 200 جرام	(9 day)	Piece قطعة	1			
8	Sterile gauze	شاش معقم	The state of the s	Piece قطعة	3			
9	Gauze bandages and gauze rollers of different sizes.	ضمادات شاش وبكرات شاش بأحجام مختلفة		Piece قطعة	2			
10	Antiseptic liquid Povidone 1	بوفيدون سائل مطهر بوفيدون 1		Piece قطعة	2			
11	Instant cold compress	كمادة باردة فورية		Piece قطعة	2			
12	Sharp scissors	مقص حاد		Piece قطعة	1			
13	Plastic tweezers	ملاقط بلاستيك		Piece قطعة	1			
14	Antiseptic cleansing wipes (sting free)	مناديل التنظيف المطهرة (خالية من اللدغات)	100pm) Soft Moist Cleaning Wipes	packet عبوة	1			
15	Disposable plastic gloves	قفازات بلاستيكية للاستخدام مرة واحدة		packet عبوة	1			
16	disposable face mask	قناع الوجه القابل للاستخدام مرة واحدة		packet عبوة	1			
المجموع / Total								